



**UNIMARC Concise Authorities Format
(2009)**

CONTENTS

RECORD LABEL.....	3
0-- IDENTIFICATION BLOCK	3
1-- CODED INFORMATION BLOCK.....	5
CONTROL SUBFIELDS.....	7
2-- AUTHORIZED ACCESS POINT BLOCK.....	9
3-- NOTES BLOCK	15
4-- VARIANT ACCESS POINT BLOCK	17
5-- RELATED ACCESS POINT BLOCK	23
6-- CLASSIFICATION AND ENTITY HISTORY BLOCK	30
7-- AUTHORIZED ACCESS POINT IN OTHER LANGUAGE AND/OR SCRIPT BLOCK	32
8-- SOURCE INFORMATION BLOCK.....	38
9-- NATIONAL USE BLOCK	40

UNIMARC Concise Authorities Format (2009)

The following list represents the state of the format as published in the third edition (2009).
Fields are optional unless marked as mandatory.

RECORD LABEL (Mandatory. Not repeatable)

0-4 Record Length

5 Record Status

c = corrected or revised record
d = deleted record
n = new record

6-9 Implementation Codes

6 Type of Record

x = authority entry record
y = reference entry record
z = general explanatory entry record

7-8 Undefined

9 Type of entity

a = personal name entry
b = corporate name entry
c = territorial or geographical name
d = trademark
e = family name
f = preferred title
g = collective preferred title
h = name/title
i = name/collective preferred title
j = topical subject
k = place access
l = form, genre or physical characteristics

10 Indicator Length (always '2')

11 Subfield Identifier Length (always '2')

12-16 Base Address of Data

17-19 Additional Record Definition

17 Encoding Level

= full
3 = partial

18-19 Undefined

20-23 Directory Map

20 Length of "length of field" (always '4')

21 Length of "starting character position" (always '5')

22-23 Undefined

0-- IDENTIFICATION BLOCK

001 Record Identifier (Mandatory. Not repeatable)

Indicators: None
Subfields: None

-
- 003 Persistent Record Identifier (Not repeatable)**
Indicators: None
Subfields: None
- 005 Version Identifier (Not repeatable)**
Indicators: None
Subfields: None
- 015 International Standard Authority Data Number (Obsolete)**
- 035 Other System Control Numbers (Repeatable)**
Indicators: blank
Subfields:
 \$a System control number (Not repeatable)
 \$z Cancelled or invalid control number (Repeatable)
- 036 Music Incipit (Repeatable)**
Indicators: blank
Subfields:
 \$a Number of work (2 characters. Mandatory. Not repeatable)
 \$b Number of movement (2 characters. Mandatory. Not repeatable)
 \$c Number of incipit (2 characters. Mandatory. Not repeatable)
 \$d Voice/instrument (Mandatory if 036 \$p is present. Not repeatable)
 \$e Role (Not repeatable)
 \$f Movement caption/heading (Repeatable)
 \$g Key or mode (Not repeatable)
 \$m Clef (Mandatory if 036 \$p is present, otherwise void. Not repeatable)
 \$n Key signature (Not repeatable)
 \$o Time signature (Not repeatable)
 \$p Musical notation (Not repeatable)
 \$q Comments (free text) (Repeatable)
 \$r Codified note (1 character. Not repeatable)
 \$t Text incipit (Repeatable)
 \$u Uniform Resource Identifier (Repeatable)
 \$z Language of text (3 characters. Repeatable)
 \$2 System code (Mandatory if 036 \$p is present. Not repeatable)
 pe = plaine & easie code
 da = DARMS code
- 050 International Standard Text Code (ISTC) (Not repeatable)**
Indicators: blank
Subfields:
 \$a Number (ISTC) (Mandatory unless \$z is present. Not repeatable)
 \$z Erroneous ISTC (Repeatable)
- 051 International Standard Musical Work Code (ISWC) (Not repeatable)**
Indicators: blank
Subfields:
 \$a Number (ISWC) (Mandatory unless \$z is present. Not repeatable)
 \$z Erroneous ISWC (Repeatable)
- 052 International Standard Audiovisual Number (ISAN) (Not repeatable)**
Indicators: blank
Subfields:
 \$a Number (ISAN) (Mandatory unless \$z is present. Not repeatable)
 \$z Erroneous ISAN (Repeatable)
- 061 International Standard Recording Code (ISRC) (Not repeatable)**
Indicators: blank
Subfields:
-

\$a Number (ISRC) (Mandatory unless \$z is present. Not repeatable)
 \$z Erroneous ISRC (Repeatable)

1-- CODED INFORMATION BLOCK

100 General Processing Data (Mandatory. Not repeatable)

Indicators: blank

Subfields:

\$a General processing data (Mandatory. Not repeatable)
 \$a/0-7 Date Entered on File (Mandatory)
 \$a/8 Status of Authorized Access Point Code
 a = established
 c = provisional
 x = not applicable
 \$a/9-11 Language of Cataloguing (Mandatory)
 \$a/12 Transliteration Code
 a = ISO transliteration scheme
 b = other
 c = multiple transliterations: ISO or other schemes.
 d = transliteration table established by the National Bibliographic Agency
 e = transliteration without any identified transliteration table
 f = other identified transliteration scheme(s)
 y = no transliteration scheme used
 \$a/13-16 Character Set (Mandatory)
 01 = ISO 646, IRV version (basic Latin set)
 02 = ISO Registration #37 (basic Cyrillic set) (Obsolete)
 03 = ISO 5426 (extended Latin set)
 04 = ISO 5427 (extended Cyrillic set)
 05 = ISO 5428 (Greek set)
 06 = ISO 6438 (African coded character set)
 07 = ISO 10586 (Georgian character set)
 08 = ISO 8957 (Hebrew set) Table 1
 09 = ISO 8957 (Hebrew set) Table 2
 10 = [Reserved]
 11 = ISO 5426-2 (Latin characters used in minor European languages and obsolete typography)
 50 = ISO 10646 Level 3
 \$a/17-20 Additional Character Set
 \$a/21-22 Script of Cataloguing
 ba = Latin
 ca = Cyrillic
 da = Japanese – script unspecified
 db = Japanese – kanji
 dc = Japanese – kana
 ea = Chinese
 fa = Arabic
 ga = Greek
 ha = Hebrew
 ia = Thai
 ja = Devanagari
 ka = Korean
 la = Tamil
 ma = Georgian
 mb = Armenian
 zz = Other
 \$a/23 Direction of Script of Cataloguing
 0 = left to right
 1 = right to left

101 Language of the Entity (Not repeatable)

Indicators: blank

Subfields:

\$a Language of or language used by the entity (Mandatory. Repeatable)
 \$c Language of the expression (Repeatable)

102 Nationality of the Entity (Mandatory when applicable. Not repeatable)

Indicators: blank

Subfields:

- \$a Country of nationality (Mandatory. Repeatable)
- \$b Locality (Repeatable)

106 Coded Data Field: Personal / Corporate / FamilyName / Trademark / Printer/Publisher Device Used As Subject Access Point (Not repeatable)

Indicators: blank

Subfields:

- \$a Coded data – use in subject access point (1 character. Mandatory. Not repeatable)
 - 0 = may be used as subject access point
 - 1 = cannot be used as subject access point
 - 2 = may be used only as subject access point
- \$b Coded data – use in subject access point as base access point or as subdivision (1 character. Not repeatable)
 - # = not applicable
 - 0 = can be used either as base access point or as subdivision
 - 1 = can be used only as base access point
 - 2 = can be used only as subdivision
- \$c Coded data – use in topical subject access point with a geographical subdivision (1 character. Not repeatable)
 - # = not applicable
 - 0 = cannot be used with a geographical subdivision
 - 1 = the access point allows a geographical subdivision, whether it is used as base access point or as subdivision
 - 2 = the access point can be used with a geographical subdivision only if used as base access point
 - 3 = the access point can be used with a geographical subdivision only if used as subdivision

120 Coded Data Field: Personal Name (Not repeatable)

Indicators: blank

Subfields:

- \$a Coded data: personal names (2 characters. Not repeatable)
- \$a/0 Gender of Entity
 - a = female
 - b = male
 - c = transgender
 - u = unknown
 - x = not applicable
- \$a/1 Differentiated or Undifferentiated Personal Name
 - a = differentiated personal name
 - b = undifferentiated personal name

123 Coded Data Field: Territorial or Geographical Name (Repeatable)

Indicators: blank

Subfields:

- \$d Co-ordinates – Westernmost Longitude (Not repeatable)
- \$e Co-ordinates – Easternmost Longitude (Not repeatable)
- \$f Co-ordinates – Northernmost Latitude (Not repeatable)
- \$g Co-ordinates – Southernmost Latitude (Not repeatable)
- \$d to \$ g/0 Hemisphere
 - w = west
 - e = east
 - n = north
 - s = south
- \$d to \$g/1-3 Degree
- \$d to \$g/4-5 Minute
- \$d to \$g/6-7 Second

150 Coded Data Field: Corporate Name (Not repeatable)

Indicators: blank

Subfields:

- \$a Type of government agency (1 character. Mandatory. Not repeatable)
 a = federal/national
 b = state/province
 c = county/department
 d = local (municipal, etc.)
 e = multi-local (interstate compacts, etc., below the national level)
 f = intergovernmental
 g = government in exile or clandestine
 h = level not determined
 u = unknown
 y = not a government organization
 z = other government level
- \$b Conference or meeting code (1 character. Not repeatable)
 0 = the corporate body is not a conference/meeting
 1 = the corporate body is conference/meeting

152 RULES (Mandatory. Not repeatable)

Indicators: blank

Subfields:

- \$a Cataloguing rules (Not repeatable)
 \$b Subject system (Not repeatable)

154 Coded Data Field: Title (Not repeatable)

Indicators: blank

Subfields:

- \$a Title processing data (2 characters. Mandatory. Not repeatable)
 \$a/0 Type of Series Code (1 character)
 a = monographic series
 b = multipart item
 c = series-like phrase (not to be considered a series)
 x = not applicable
 z = other
- \$a/1 Type of Entity Code (1 character)
 a = work
 b = expression
 x = not applicable

160 Geographic Area Code (Not repeatable)

Indicators: blank

Subfields:

- \$a Geographic area code (Mandatory. Repeatable)

CONTROL SUBFIELDS

- \$0 Instruction Phrase** (Not repeatable. May be used with 4-- variant and 5-- related access point fields.)
- \$1 Linking Data** (Repeatable)
- \$2 System Code** (Not repeatable. May be used in 4-- variant and 5-- related access point or 7-- authorized access point in other language and/or script fields.)
- \$3 Authority Record Identifier** (Not repeatable. It may be used in 5-- related access point and 7-- authorized access point in other language and/or script and 4-- variant access point fields, and 6-- classification and entity history block.)

\$5 Relationship Control (Not repeatable. This subfield may be used in 4-- and 5-- access point fields.)**\$5/0 Name Relationship Code**

a = earlier name
 b = later name
 c = official name
 d = acronym / initial / abbreviation
 e = pseudonym
 f = real name
 g = broader term or name
 h = narrower term or name
 i = name in religion
 j = married name
 k = name before marriage
 l = shared pseudonym
 m = secular name
 n = different rule form of a name (if used, \$2 is mandatory)
 o = attributed name / conventional title of a work
 x = not applicable
 z = other

\$5/1 Reference Suppression Code

0 = suppress reference
 x = not applicable

\$5/2 Specific Relationship Code for Works

a = original work
 b = variation or version of a work
 c = adaptation or modification of a work
 d = whole work
 e = part of the larger work
 f = supplement or complement work
 g = related/accompanied work
 h = successor or sequel/later work
 i = predecessor or earlier work
 k = works with common characteristics
 x = not applicable
 z = other

\$5/3 Specific Relationship Code for Agents

c = descendant family relationship
 d = progenitor family relationship
 e = relationship in marriage
 j = sibling relationship
 g = parent relationship
 h = child relationship
 k = member (is member of)
 l = has member
 m = founder (has founded)
 n = founded by
 p = subordinate corporate body
 q = larger corporate body
 s = owner (owns)
 t = owned by
 z = other

\$6 Interfield Linking Data (Not repeatable. This subfield may be used in the 3-- information note and 4-- and 5-- access point fields.)**\$6/0 Linking Explanation Code** (1 character)

a = alternate script
 z = other

\$6/1-2 Linking Number (2 characters)**\$6/3-5 Tag of Linked Field** (3 characters)

\$7 Script of Cataloguing and Script of the Base Access Point (Mandatory for parallel script data. Not repeatable. The \$7 subfield may be used with 2-- authorized access points, 3-- information note, 4-- variant and 5-- related access points, and 7-- authorized access point in other language and/or script fields.)

\$7/0-1 and \$7/4-5	Script (2 characters)	
	ba = Latin	ha = Hebrew
	ca = Cyrillic	ia = Thai
	da = Japanese -- script unspecified	ja = Devanagari
	db = Japanese – kanji	ka = Korean
	dc = Japanese – kana	la = Tamil
	ea = Chinese	ma = Georgian
	fa = Arabic	mb = Armenian
	ga = Greek	zz = Other
\$7/2 and \$7/6	Direction of the Script (1 character)	
	0 = left to right	
	1 = right to left	
\$7/3 and \$7/7	Transliteration Scheme (1 character)	
	a = ISO transliteration scheme	
	b = Other	
	c = Multiple transliterations: ISO or other schemes	
	d = Transliteration table established by the National Bibliographic Agency	
	e = Transliteration without any identified transliteration table	
	f = Other identified transliteration scheme(s)	
	y = Not applicable (no transliteration scheme used)	

\$8 Language of Cataloguing and Language of the Base Access Point (Mandatory in each 7-- authorized access point in other language and/or script when parallel access points or parallel data. Optional in 2--, 4--, 5--. Not repeatable)

\$8/0-2 Language of Cataloguing (3 characters)

\$8/3-5 Language of the Base Access Point (3 characters)

2-- AUTHORIZED ACCESS POINT BLOCK

200 Authorized Access Point – Personal Name (Repeatable for alternative script forms)

Indicator 1: blank

Indicator 2: specifies the way the name is entered:

0 Name entered under forename or direct order

1 Name entered under surname

Data Subfields

\$a Entry element (Mandatory if field is present. Not repeatable)

\$b Part of name other than entry element (Not repeatable)

\$c Additions to names other than dates (Repeatable)

\$d Roman numerals (Not repeatable)

\$f Dates (Not repeatable)

\$g Expansion of initials of forename (Not repeatable)

\$4 Relator code (Repeatable)

\$j Form subdivision (Repeatable)

\$x Topical subdivision (Repeatable)

\$y Geographical subdivision (Repeatable)

\$z Chronological subdivision (Repeatable)

Control Subfields

- \$7 Script of cataloguing and script of the base access point (Not repeatable)
- \$8 Language of cataloguing and language of the base access point (Not repeatable)

210 Authorized Access Point – Corporate Body Name (Repeatable for alternative script forms)

Indicator 1: specifies the type of corporate body:

- 0 Corporate name
- 1 Meeting

Indicator 2: specifies the way the name is entered:

- 0 Name in inverted form
- 1 Name entered under place or jurisdiction
- 2 Name entered under name in direct order

Data Subfields

- \$a Entry element (Mandatory if field is present. Not repeatable)
- \$b Subdivision (Repeatable)
- \$c Addition to name or qualifier (Repeatable)
- \$d Number of meeting and/or number of part of meeting (Not repeatable)
- \$e Location of meeting (Not repeatable)
- \$f Date of meeting (Not repeatable)
- \$g Inverted element (Not repeatable)
- \$h Part of name other than entry element and inverted element (Not repeatable)
- \$4 Relator code (Repeatable)
- \$j Form subdivision (Repeatable)
- \$x Topical subdivision (Repeatable)
- \$y Geographical subdivision (Repeatable)
- \$z Chronological subdivision (Repeatable)

Control Subfields

- \$7 Script of cataloguing and script of the base access point (Not repeatable)
- \$8 Language of cataloguing and language of the base access point (Not repeatable)

215 Authorized Access Point – Territorial or Geographical Name (Repeatable for alternative script forms)

Indicators: blank

Data Subfields

- \$a Entry element (Mandatory if field is present. Not repeatable)
- \$j Form subdivision (Repeatable)
- \$x Topical subdivision (Repeatable)
- \$y Geographical subdivision (Repeatable)
- \$z Chronological subdivision (Repeatable)

Control Subfields

- \$7 Script of cataloguing and script of the base access point (Not repeatable)
- \$8 Language of cataloguing and language of the base access point (Not repeatable)

216 Authorized Access Point – Trademark (Repeatable for alternative script forms)

Indicators: blank

Data Subfields

- \$a Data element (Mandatory. Not repeatable)

- \$f Dates (Not repeatable)
- \$c Qualification (Repeatable)
- \$j Form subdivision (Repeatable)
- \$x Topical subdivision (Repeatable)
- \$y Geographical subdivision (Repeatable)
- \$z Chronological subdivision (Repeatable)

Control Subfields

- \$7 Script of cataloguing and script of the base access point (Not repeatable)
- \$8 Language of cataloguing and language of the base access point (Not repeatable)

217 Authorized Access Point – Printer/Publisher Device (Repeatable for alternative script forms)

Indicators: blank

Data Subfields

- \$a Printer/publisher device description (Not repeatable)
- \$b Motto (Repeatable)
- \$c Standard citation (Repeatable)
- \$d Size (Not repeatable)
- \$f Date (Not repeatable)
- \$g Iconographic term (Repeatable)
- \$j Form subdivision (Repeatable)
- \$x Topical subdivision (Repeatable)
- \$y Geographical subdivision (Repeatable)
- \$z Chronological subdivision (Repeatable)

Control Subfields

- \$7 Script of cataloguing and script of the base access point (Not repeatable)
- \$8 Language of cataloguing and language of the base access point (Not repeatable)

220 Authorized Access Point – Family Name (Repeatable for alternative script forms)

Indicators: blank

Data Subfields

- \$a Entry element (Mandatory. Not repeatable)
- \$c Type of family (Not repeatable)
- \$d Places associated with the family (Repeatable)
- \$f Dates (Not repeatable)
- \$4 Relator code (Repeatable)
- \$j Form subdivision (Repeatable)
- \$x Topical subdivision (Repeatable)
- \$y Geographical subdivision (Repeatable)
- \$z Chronological subdivision (Repeatable)

Control Subfields

- \$7 Script of cataloguing and script of the base access point (Not repeatable)
- \$8 Language of cataloguing and language of the base access point (Not repeatable)

230 Authorized Access Point – Title (Repeatable for alternative script forms)

Indicators: blank

Data Subfields

\$a	Entry element (Mandatory. Not repeatable)
\$b	General material designation (Repeatable)
\$h	Number of section or part (Repeatable)
\$i	Name of section or part (Repeatable)
\$k	Date of publication (Not repeatable)
\$l	Form subdivision (Not repeatable)
\$m	Language (Not repeatable)
\$n	Miscellaneous information (Repeatable)
\$q	Version (or date of version) (Not repeatable)
\$r	Medium of performance (for music) (Repeatable)
\$s	Numeric designation (for music) (Repeatable)
\$u	Key (for music) (Not repeatable)
\$w	Arranged statement (for music) (Not repeatable)
\$j	Form subdivision (Repeatable)
\$x	Topical subdivision (Repeatable)
\$y	Geographical subdivision (Repeatable)
\$z	Chronological subdivision (Repeatable)

Control Subfields

\$7	Script of cataloguing and script of the base access point (Not repeatable)
\$8	Language of cataloguing and language of the base access point (Not repeatable)

235 Authorized Access Point – Collective Title (Repeatable for alternative script forms)

Indicator 1: specifies the type of collective title:

- 0 Complete collected works
- 1 Selected works
- 2 Selections

Indicator 2: blank

Data Subfields

\$a	Collective title (Mandatory. Not repeatable)
\$b	General material designation (Repeatable)
\$e	Collective subtitle (Not repeatable)
\$k	Date of publication (Not repeatable)
\$m	Language (Not repeatable)
\$r	Medium of performance (for music) (Repeatable)
\$s	Numeric designation (for music) (Repeatable)
\$u	Key (for music) (Not repeatable)
\$w	Arranged statement (for music) (Not repeatable)
\$j	Form subdivision (Repeatable)
\$x	Topical subdivision (Repeatable)
\$y	Geographical subdivision (Repeatable)
\$z	Chronological subdivision (Repeatable)

Control Subfields

\$7	Script of cataloguing and script of the base access point (Not repeatable)
\$8	Language of cataloguing and language of the base access point (Not repeatable)

240 Authorized Access Point – Name/Title (Repeatable for alternative script forms)

Indicators: blank

A) Subfields: Embedded Fields Technique

Data Subfields

\$1 Linking data (Repeatable)

Control Subfields

\$7 Script of cataloguing and script of the base access point (Not repeatable)

\$8 Language of cataloguing and language of the base access point (Not repeatable)

B) Subfields: Standard Subfields Technique

Data Subfields

\$a Name (Not repeatable)

\$t Title (Not repeatable)

\$j Form subdivision (Repeatable)

\$x Topical subdivision (Repeatable)

\$y Geographical subdivision (Repeatable)

\$z Chronological subdivision (Repeatable)

Control Subfields

\$7 Script of cataloguing and script of the base access point (Not repeatable)

\$8 Language of cataloguing and language of the base access point (Not repeatable)

243 Authorized Access Point – Conventional Name/Title for Legal and Religious Texts (Not repeatable)

Indicator 1: blank

Indicator 2: specifies the form of conventional name:

1 Name entered under country or other geographical name

2 Name entered under other form

Data Subfields

\$a Entry Element (Mandatory if field is present. Not repeatable)

\$b Subdivision (Repeatable)

\$c Addition to Name or Qualifier (Repeatable)

\$e Name of the other party (Not repeatable)

\$f Date of legal issue or version, or date of signing (Repeatable)

\$i Name of section or part (Repeatable)

\$l Form subheading (Repeatable)

\$n Miscellaneous information (Repeatable)

\$t Conventional title (Not repeatable)

\$j Form subdivision (Repeatable)

\$x Topical subdivision (Repeatable)

\$y Geographical subdivision (Repeatable)

\$z Chronological subdivision (Repeatable)

Control Subfields

\$7 Script of cataloguing and script of the base access point (Not repeatable)

\$8 Language of cataloguing and language of the base access point (Not repeatable)

245 Authorized Access Point – Name/Collective Title (Repeatable for alternative script forms)

Indicators: blank

A) Subfields: Embedded Fields Technique

Data Subfields

\$1 Linking data (Repeatable)

Control Subfields

\$7 Script of cataloguing and script of the base access point (Not repeatable)

\$8 Language of cataloguing and language of the base access point (Not repeatable)

B) Subfields: Standard Subfields Technique

Data Subfields

\$a Name (Not repeatable)

\$t Collective title (Not repeatable)

\$j Form subdivision (Repeatable)

\$x Topical subdivision (Repeatable)

\$y Geographical subdivision (Repeatable)

\$z Chronological subdivision (Repeatable)

Control Subfields

\$7 Script of cataloguing and script of the base access point (Not repeatable)

\$8 Language of cataloguing and language of the base access point (Not repeatable)

250 Authorized Access Point – Topical Subject (Repeatable for alternative script forms)

Indicators: blank

Data Subfields

\$a Topical subject or subject category (Not repeatable)

\$n Subject category code (Repeatable)

\$m Subject category subdivision code (Repeatable)

\$j Form subdivision (Repeatable)

\$x Topical subdivision or subject category subdivision text (Repeatable)

\$y Geographical subdivision (Repeatable)

\$z Chronological subdivision (Repeatable)

Control Subfields

\$7 Script of cataloguing and script of the base access point (Not repeatable)

\$8 Language of cataloguing and language of the base access point (Not repeatable)

260 Authorized Access Point – Place and Date of Publication, Performance, Provenance, etc. (Repeatable for alternative script forms)

Indicators: blank

Data Subfields

\$a Country (nation state) (Not repeatable)

\$b State or province, etc. (Not repeatable)

\$c Intermediate political jurisdiction (Repeatable)

\$d City, etc. (Not repeatable)

\$e Venue (Repeatable)

\$f Date (Repeatable)

\$g Season (Not repeatable)

\$h Occasion (Not repeatable)

\$i Final date (Not repeatable)

\$k Subsection of city, etc. (Repeatable)

\$m Other geographical regions or features (Repeatable)

\$n Extraterrestrial areas (Repeatable)

- \$o Geographical area (Repeatable)
- Control Subfields
 - \$7 Script of cataloguing and script of the base access point (Not repeatable)
 - \$8 Language of cataloguing and language of the base access point (Not repeatable)

280 Authorized Access Point – Form, Genre or Physical Characteristics (Repeatable for alternative script forms)

Indicator 1: blank

Indicator 2: specifies the type of the entity:

- # Not defined
- 0 Work
- 2 Manifestation
- 3 Item

Data Subfields

- \$a Entry element (Not repeatable)
- \$j Form subdivision (Repeatable)
- \$x Topical subdivision (Repeatable)
- \$y Geographical subdivision (Repeatable)
- \$z Chronological Subdivision (Repeatable)

Control Subfields

- \$7 Script of cataloguing and script of the base access point (Not repeatable)
- \$8 Language of cataloguing and language of the base access point (Not repeatable)

3-- NOTES BLOCK

300 Information Note (Repeatable)

Indicator 1: specifies the type of note:

- 0 Note concerns name or title use of access point
- 1 Note concerns subject use of access point

Indicator 2: blank

Data Subfields

- \$a Information note (Mandatory. Not repeatable)

Control Subfields

- \$6 Interfield linking data (Not repeatable)
- \$7 Script of cataloguing and base access point (Not repeatable)

305 Textual See Also Reference Note (Repeatable)

Indicator 1: specifies the type of note:

- 0 Note concerns name or title use of access point
- 1 Note concerns subject use of access point

Indicator 2: blank

Data Subfields

- \$a Instruction phrase (Repeatable)
- \$b Access point referred to (Repeatable)

Control Subfields

- \$6 Interfield linking data (Not repeatable)
- \$7 Script of cataloguing and script of the base access point (Not repeatable)

310 Textual See Reference Note (Repeatable)

Indicator 1: specifies the type of note:

0 Note concerns name or title use of access point

1 Note concerns subject use of access point

Indicator 2: blank

Data Subfields

\$a Instruction phrase (Repeatable)

\$b Access point referred to (Repeatable)

Control Subfields

\$6 Interfield linking data (Not repeatable)

\$7 Script of cataloguing and script of the base access point (Not repeatable)

320 General Explanatory Reference Note (Not repeatable)

Indicators: blank

Data Subfields

\$a General explanatory reference note (Repeatable)

Control Subfields

\$6 Interfield linking data (Not repeatable)

\$7 Script of cataloguing and script of the base access point (Not repeatable)

330 General Scope Note (Repeatable)

Indicator 1: specifies the type of note:

0 Note concerns name or title use of access point

1 Note concerns subject use of access point

Indicator 2: blank

Data Subfields

\$a General scope note (Not repeatable)

Control Subfields

\$6 Interfield linking data (Not repeatable)

\$7 Script of cataloguing and script of the base access point (Not repeatable)

340 Biography and Activity Note (Repeatable)

Indicators: blank

Data Subfields

\$a Biographical note (Not repeatable)

\$b Activity note (Not repeatable)

\$p Affiliation/Address (Repeatable)

Control Subfields

\$6 Interfield Linking Data (Not repeatable)

\$7 Script of cataloguing and script of the base access point (Not repeatable)

341 Activity Note Pertaining to Printer/Publisher (Repeatable)

Indicators: blank

Data Subfields

\$a Place of activity (Not repeatable)

\$b Dates of activity (Not repeatable)

\$c Address (Repeatable)

\$d Sign (Repeatable)

Control Subfields

\$6 Interfield linking data (Not repeatable)

\$7 Script of cataloguing and script of the base access point (Not repeatable)

356 Geographical Note (Repeatable)

Indicators: blank

Data Subfields

\$a Geographical note (Not repeatable)

Control Subfields

\$6 Interfield linking data (Not repeatable)

\$7 Script of cataloguing and script of the base access point (Not repeatable)

4-- VARIANT ACCESS POINT BLOCK

400 Variant Access Point – Personal Name (Repeatable)

Indicator 1: blank

Indicator 2: specifies the way the name is entered:

0 Name entered under forename or direct order

1 Name entered under surname

Data Subfields

\$a Entry element (Not repeatable)

\$b Part of name other than entry element (Not repeatable)

\$c Additions to names other than dates (Repeatable)

\$d Roman numerals (Not repeatable)

\$f Dates (Not repeatable)

\$g Expansion of initials of forename (Not repeatable)

\$4 Relator code (Repeatable)

\$j Form subdivision (Repeatable)

\$x Topical subdivision (Repeatable)

\$y Geographical subdivision (Repeatable)

\$z Chronological subdivision (Repeatable)

Control Subfields

\$0 Instruction phrase (Not repeatable)

\$2 System code (Not repeatable)

\$3 Authority record identifier (Not repeatable)

\$5 Relationship control (Not repeatable)

\$6 Interfield linking data (Not repeatable)

\$7 Script of cataloguing and script of the base access point (Not repeatable)

\$8 Language of cataloguing and language of the base access point (Not repeatable)

410 Variant Access Point – Corporate Body Name (Repeatable)

Indicator 1: specifies the kind of corporate body:

0 Corporate name

1 Meeting

Indicator 2: specifies the way the names are entered:

0 Name in inverted form

1 Name entered under place or jurisdiction

2 Name entered under name in direct order

Data Subfields

\$a Entry element (Not repeatable)

\$b	Subdivision (Repeatable)
\$c	Addition to name or qualifier (Repeatable)
\$d	Number of meeting and/or number of part of meeting (Not repeatable)
\$e	Location of meeting (Not repeatable)
\$f	Date of meeting (Not repeatable)
\$g	Inverted element (Not repeatable)
\$h	Part of name other than entry element and inverted element (Not repeatable)
\$4	Relator code (Repeatable)
\$j	Form subdivision (Repeatable)
\$x	Topical subdivision (Repeatable)
\$y	Geographical subdivision (Repeatable)
\$z	Chronological subdivision (Repeatable)

Control Subfields

\$0	Instruction phrase (Not repeatable)
\$2	System code (Not repeatable)
\$3	Authority record identifier (Not repeatable)
\$5	Relationship control (Not repeatable)
\$6	Interfield linking data (Not repeatable)
\$7	Script of cataloguing and script of the base access point (Not repeatable)
\$8	Language of cataloguing and language of the base access point (Not repeatable)

415 Variant Access Point – Territorial or Geographical Name (Repeatable)

Indicators: blank

Data Subfields

\$a	Entry element (Not repeatable)
\$j	Form subdivision (Repeatable)
\$x	Topical subdivision (Repeatable)
\$y	Geographical subdivision (Repeatable)
\$z	Chronological subdivision (Repeatable)

Control Subfields

\$0	Instruction phrase (Not repeatable)
\$2	System code (Not repeatable)
\$3	Authority record identifier (Not repeatable)
\$5	Relationship control (Not repeatable)
\$6	Interfield linking data (Not repeatable)
\$7	Script of cataloguing and script of the base access point (Not repeatable)
\$8	Language of cataloguing and language of the base access point (Not repeatable)

416 Variant Access Point – Trademark (Repeatable)

Indicators: blank

Data Subfields

\$a	Data element (Not repeatable)
\$f	Dates (Not repeatable)
\$c	Qualification (Repeatable)
\$j	Form subdivision (Repeatable)
\$x	Topical subdivision (Repeatable)
\$y	Geographical subdivision (Repeatable)

- \$z Chronological subdivision (Repeatable)
- Control Subfields
- \$0 Instruction phrase (Not repeatable)
 - \$2 System code (Not repeatable)
 - \$3 Authority record identifier (Not repeatable)
 - \$5 Relationship control (Not repeatable)
 - \$6 Interfield linking data (Not repeatable)
 - \$7 Script of cataloguing and script of the base access point (Not repeatable)
 - \$8 Language of cataloguing and language of the base access point (Not repeatable)

417 Variant Access Point – Printer/Publisher Device (Repeatable)

Indicators: blank

Data Subfields

- \$a Printer/publisher device description (Not repeatable)
- \$b Motto (Repeatable)
- \$c Standard citation (Repeatable)
- \$d Size (Not repeatable)
- \$f Date (Not repeatable)
- \$g Iconographic term (Repeatable)
- \$j Form subdivision (Repeatable)
- \$x Topical subdivision (Repeatable)
- \$y Geographical subdivision (Repeatable)
- \$z Chronological subdivision (Repeatable)

Control Subfields

- \$0 Instruction phrase (Not repeatable)
- \$2 System code (Not repeatable)
- \$3 Authority record identifier (Not repeatable)
- \$5 Relationship control (Not repeatable)
- \$6 Interfield linking data (Not repeatable)
- \$7 Script of cataloguing and script of the base access point (Not repeatable)
- \$8 Language of cataloguing and language of the base access point (Not repeatable)

420 Variant Access Point – Family Name (Repeatable)

Indicators: blank

Data Subfields

- \$a Entry element (Not repeatable)
- \$f Dates (Not repeatable)
- \$c Type of family (Not repeatable)
- \$d Places associated with the family (Repeatable)
- \$4 Relator code (Repeatable)
- \$j Form subdivision (Repeatable)
- \$x Topical subdivision (Repeatable)
- \$y Geographical subdivision (Repeatable)
- \$z Chronological subdivision (Repeatable)

Control Subfields

- \$0 Instruction phrase (Not repeatable)
- \$2 System code (Not repeatable)
- \$3 Authority record identifier (Not repeatable)

- \$5 Relationship control (Not repeatable)
- \$6 Interfield linking data (Not repeatable)
- \$7 Script of cataloguing and script of the base access point (Not repeatable)
- \$8 Language of cataloguing and language of the base access point (Not repeatable)

430 Variant Access Point – Title (Repeatable)

Indicators: blank

Data Subfields

- \$a Entry element (Not repeatable)
- \$b General material designation (Repeatable)
- \$h Number of section or part (Repeatable)
- \$i Name of section or part (Repeatable)
- \$k Date of publication (Not repeatable)
- \$l Form subdivision (Not repeatable)
- \$m Language (Not repeatable)
- \$n Miscellaneous information (Repeatable)
- \$q Version (or date of version) (Not repeatable)
- \$r Medium of performance (for music) (Repeatable)
- \$s Numeric designation (for music) (Repeatable)
- \$u Key (for music) (Not repeatable)
- \$w Arranged statement (for music) (Not repeatable)
- \$j Form subdivision (Repeatable)
- \$x Topical subdivision (Repeatable)
- \$y Geographical subdivision (Repeatable)
- \$z Chronological subdivision (Repeatable)

Control Subfields

- \$0 Instruction phrase (Not repeatable)
- \$2 System code (Not repeatable)
- \$3 Authority record identifier (Not repeatable)
- \$5 Relationship control (Not repeatable)
- \$6 Interfield linking data (Not repeatable)
- \$7 Script of cataloguing and script of the base access point (Not repeatable)
- \$8 Language of cataloguing and language of the base access point (Not repeatable)

440 Variant Access Point – Name/Title (Repeatable)

Indicators: blank

A) Subfields: Embedded Fields Technique

Data Subfields

- \$1 Linking data (Repeatable)

Control Subfields

- \$0 Instruction phrase (Not repeatable)
- \$2 System code (Not repeatable)
- \$3 Authority record identifier (Not repeatable)
- \$5 Relationship control (Not repeatable)
- \$6 Interfield linking data (Not repeatable)
- \$7 Script of cataloguing and script of the base access point (Not repeatable)
- \$8 Language of cataloguing and language of the base access point (Not repeatable)

B) Subfields: Standard Subfields Technique

Data Subfields

- \$a Name (Not repeatable)
- \$t Title (Not repeatable)
- \$j Form subdivision (Repeatable)
- \$x Topical subdivision (Repeatable)
- \$y Geographical subdivision (Repeatable)
- \$z Chronological subdivision (Repeatable)

Control Subfields

- \$7 Script of cataloguing and script of the base access point (Not repeatable)
- \$8 Language of cataloguing and language of the base access point (Not repeatable)

443 Variant Access Point – Conventional Name/Title for Legal and Religious Texts (Repeatable)

Indicator 1: blank

Indicator 2: specifies the form of conventional name/title:

- 1 Name entered under country or other geographical name
- 2 Name entered under other form

Data Subfields

- \$a Entry Element (Not repeatable)
- \$b Subdivision (Repeatable)
- \$c Addition to Name or Qualifier (Repeatable)
- \$e Name of the other party (Not repeatable)
- \$f Date of legal issue or version, or date of the signing (Repeatable)
- \$i Name of section or part (Repeatable)
- \$l Form Subheading (Repeatable)
- \$n Miscellaneous information (Repeatable)
- \$t Conventional title (Not repeatable)
- \$j Form subdivision (Repeatable)
- \$x Topical subdivision (Repeatable)
- \$y Geographical subdivision (Repeatable)
- \$z Chronological subdivision (Repeatable)

Control Subfields

- \$0 Instruction phrase (Repeatable)
- \$2 System code (Not repeatable)
- \$3 Authority record identifier (Not repeatable)
- \$5 Relationship control (Not repeatable)
- \$6 Interfield linking data (Repeatable)
- \$7 Script of cataloguing and script of the base access point (Not repeatable)
- \$8 Language of cataloguing and language of the base access point (Not repeatable)

445 Variant Access Point – Name/Collective Title (Repeatable)

Indicators: blank

A) Subfields: Embedded Fields Technique

Data Subfields

- \$1 Linking data (Repeatable)

Control Subfields

- \$0 Instruction phrase (Not repeatable)

- \$2 System code (Not repeatable)
- \$3 Authority record identifier (Not repeatable)
- \$5 Relationship control (Not repeatable)
- \$6 Interfield linking data (Not repeatable)
- \$7 Script of cataloguing and script of the base access point (Not repeatable)
- \$8 Language of cataloguing and language of the base access point (Not repeatable)

B) Subfields: Standard Subfields Technique

Data Subfields

- \$a Name (Not repeatable)
- \$t Title (Not repeatable)
- \$j Form subdivision (Repeatable)
- \$x Topical subdivision (Repeatable)
- \$y Geographical subdivision (Repeatable)
- \$z Chronological subdivision (Repeatable)

Control Subfields

- \$7 Script of cataloguing and script of the base access point (Not repeatable)
- \$8 Language of cataloguing and language of the base access point (Not repeatable)

450 Variant Access Point – Topical Subject (Repeatable)

Indicators: blank

Data Subfields

- \$a Topical subject (Not repeatable)
- \$n Subject category code (Repeatable)
- \$m Subject category subdivision code (Repeatable)
- \$j Form subdivision (Repeatable)
- \$x Topical subdivision (Repeatable)
- \$y Geographical subdivision (Repeatable)
- \$z Chronological subdivision (Repeatable)

Control Subfields

- \$0 Instruction phrase (Not repeatable)
- \$2 System code (Not repeatable)
- \$3 Authority record identifier (Not repeatable)
- \$5 Relationship control (Not repeatable)
- \$6 Interfield linking data (Not repeatable)
- \$7 Script of cataloguing and script of the base access point (Not repeatable)
- \$8 Language of cataloguing and language of the base access point (Not repeatable)

460 Variant access point – Place and date of publication, performance, provenance etc. (Repeatable)

Indicators: blank

Data Subfields

- \$a Country (nation state) (Not repeatable)
- \$b State or province, etc. (Not repeatable)
- \$c Intermediate political jurisdiction (Repeatable)
- \$d City, etc. (Not repeatable)
- \$e Venue (Repeatable)
- \$f Date (Repeatable)

- \$g Season (Not repeatable)
 - \$h Occasion (Not repeatable)
 - \$i Final date (Not repeatable)
 - \$k Subsection of city, etc. (Repeatable)
 - \$m Other geographical regions or features (Repeatable)
 - \$n Extraterrestrial areas (Repeatable)
 - \$o Geographical areas such as world, hemisphere, continent (Repeatable)
- Control Subfields
- \$0 Instruction phrase (Not repeatable)
 - \$2 System code (Not repeatable)
 - \$3 Authority record identifier (Not repeatable)
 - \$5 Relationship control (Not repeatable)
 - \$6 Interfield linking data (Not repeatable)
 - \$7 Script of cataloguing and script of the base access point (Not repeatable)
 - \$8 Language of cataloguing and language of the base access point (Not repeatable)

480 Variant Access Point – Form, Genre or Physical Characteristics (Repeatable)

Indicator 1: blank

Indicator 2: specifies the type of entity:

- # Not defined
- 0 Work
- 2 Manifestation
- 3 Item

Data Subfields

- \$a Entry Element (Not repeatable)
- \$j Form Subdivision (Repeatable)
- \$x Topical Subdivision (Repeatable)
- \$y Geographical Subdivision (Repeatable)
- \$z Chronological Subdivision (Repeatable)

Control Subfields

- \$0 Instruction phrase (Not repeatable)
- \$2 System code (Not repeatable)
- \$3 Authority record identifier (Not repeatable)
- \$5 Relationship control (Not repeatable)
- \$6 Interfield linking data (Not repeatable)
- \$7 Script of cataloguing and script of the base access point (Not repeatable)
- \$8 Language of cataloguing and language of the base access point (Not repeatable)

5-- RELATED ACCESS POINT BLOCK

500 Related Access Point – Personal Name (Repeatable)

Indicator 1: blank

Indicator 2: specifies the way the name is entered:

- 0 Name entered under forename or direct order
- 1 Name entered under surname

Data Subfields

- \$a Entry element (Not repeatable)

- \$b Part of name other than entry element (Not repeatable)
- \$c Additions to names other than dates (Repeatable)
- \$d Roman numerals (Not repeatable)
- \$f Dates (Not repeatable)
- \$g Expansion of initials of forename (Not repeatable)
- \$4 Relator code (Repeatable)
- \$j Form subdivision (Repeatable)
- \$x Topical subdivision (Repeatable)
- \$y Geographical subdivision (Repeatable)
- \$z Chronological subdivision (Repeatable)

Control Subfields

- \$0 Instruction phrase (Not repeatable)
- \$2 System code (Not repeatable)
- \$3 Authority record identifier (Not repeatable)
- \$5 Relationship control (Not repeatable)
- \$6 Interfield linking data (Not repeatable)
- \$7 Script of cataloguing and script of the base access point (Not repeatable)
- \$8 Language of cataloguing and language of the base access point (Not repeatable)

510 Related Access Point – Corporate Body Name (Repeatable)

Indicator 1: specifies the kind of corporate body:

- 0 Corporate name
- 1 Meeting

Indicator 2: specifies the way the names are entered:

- 0 Name in inverted form
- 1 Name entered under place or jurisdiction
- 2 Name entered under name in direct order

Data Subfields

- \$a Entry element (Not repeatable)
- \$b Subdivision (Repeatable)
- \$c Addition to name or qualifier (Repeatable)
- \$d Number of meeting and/or number of part of meeting (Not repeatable)
- \$e Location of meeting (Not repeatable)
- \$f Date of meeting (Not repeatable)
- \$g Inverted element (Not repeatable)
- \$h Part of name other than entry element and inverted element (Not repeatable)
- \$4 Relator code (Repeatable)
- \$j Form subdivision (Repeatable)
- \$x Topical subdivision (Repeatable)
- \$y Geographical subdivision (Repeatable)
- \$z Chronological subdivision (Repeatable)

Control Subfields

- \$0 Instruction phrase (Not repeatable)
- \$2 System code (Not repeatable)
- \$3 Authority record identifier (Not repeatable)
- \$5 Relationship control (Not repeatable)
- \$6 Interfield linking data (Not repeatable)
- \$7 Script of cataloguing and script of the base access point (Not repeatable)

\$8 Language of cataloguing and language of the base access point (Not repeatable)

515 Related Access Point – Territorial or Geographical Name (Repeatable)

Indicators: blank

Data Subfields

\$a Entry element (Not repeatable)
\$j Form subdivision (Repeatable)
\$x Topical subdivision (Repeatable)
\$y Geographical subdivision (Repeatable)
\$z Chronological subdivision (Repeatable)

Control Subfields

\$0 Instruction phrase (Not repeatable)
\$2 System code (Not repeatable)
\$3 Authority record identifier (Not repeatable)
\$5 Relationship control (Not repeatable)
\$6 Interfield linking data (Not repeatable)
\$7 Script of cataloguing and script of the base access point (Not repeatable)
\$8 Language of cataloguing and language of the base access point (Not repeatable)

516 Related Access Point – Trademark (Repeatable)

Indicators: blank

Data Subfields

\$a Data element (Not repeatable)
\$f Dates (Not repeatable)
\$c Qualification (Repeatable)
\$j Form Subdivision (Repeatable)
\$x Topical subdivision (Repeatable)
\$y Geographical subdivision (Repeatable)
\$z Chronological subdivision (Repeatable)

Control Subfields

\$0 Instruction phrase (Not repeatable)
\$2 System code (Not repeatable)
\$3 Authority record identifier (Not repeatable)
\$5 Relationship control (Not repeatable)
\$6 Interfield linking data (Not repeatable)
\$7 Script of cataloguing and script of the base access point (Not repeatable)
\$8 Language of cataloguing and language of the base access point (Not repeatable)

517 Related Access Point – Printer/Publisher Device (Repeatable)

Indicators: blank

Data Subfields

\$a Printer/publisher device description (Not repeatable)
\$b Motto (Repeatable)
\$c Standard citation (Repeatable)
\$d Size (Not repeatable)
\$f Date (Not repeatable)
\$g Iconographic term (Repeatable)

- \$j Form subdivision (Repeatable)
- \$x Topical subdivision (Repeatable)
- \$y Geographical subdivision (Repeatable)
- \$z Chronological subdivision (Repeatable)

Control Subfields

- \$0 Instruction phrase (Not repeatable)
- \$2 System code (Not repeatable)
- \$3 Authority record identifier (Not repeatable)
- \$5 Relationship control (Not repeatable)
- \$6 Interfield linking data (Not repeatable)
- \$7 Script of cataloguing and script of the base access point (Not repeatable)
- \$8 Language of cataloguing and language of the base access point (Not repeatable)

520 Related Access Point – Family Name (Repeatable)

Indicators: blank

Data Subfields

- \$a Entry element (Not repeatable)
- \$c Type of family (Not repeatable)
- \$d Places associated with the family (Repeatable)
- \$f Dates (Not repeatable)
- \$4 Relator code (Repeatable)
- \$j Form subdivision (Repeatable)
- \$x Topical subdivision (Repeatable)
- \$y Geographical subdivision (Repeatable)
- \$z Chronological subdivision (Repeatable)

Control Subfields

- \$0 Instruction phrase (Not repeatable)
- \$2 System code (Not repeatable)
- \$3 Authority record identifier (Not repeatable)
- \$5 Relationship control (Not repeatable)
- \$6 Interfield linking data (Not repeatable)
- \$7 Script of cataloguing and script of the base access point (Not repeatable)
- \$8 Language of cataloguing and language of the base access point (Not repeatable)

530 Related Access Point – Title (Repeatable)

Indicators: blank

Data Subfields

- \$a Entry element (Not repeatable)
- \$b General material designation (Repeatable)
- \$h Number of section or part (Repeatable)
- \$i Name of section or part (Repeatable)
- \$k Date of publication (Not repeatable)
- \$l Form subdivision (Not repeatable)
- \$m Language (Not repeatable)
- \$n Miscellaneous information (Repeatable)
- \$q Version (or date of version) (Not repeatable)
- \$r Medium of performance (for music) (Repeatable)
- \$s Numeric designation (for music) (Repeatable)

- \$u Key (for music) (Not repeatable)
- \$w Arranged statement (for music) (Not repeatable)
- \$j Form subdivision (Repeatable)
- \$x Topical subdivision (Repeatable)
- \$y Geographical subdivision (Repeatable)
- \$z Chronological subdivision (Repeatable)

Control Subfields

- \$0 Instruction phrase (Not repeatable)
- \$2 System code (Not repeatable)
- \$3 Authority record identifier (Not repeatable)
- \$5 Relationship control (Not repeatable)
- \$6 Interfield linking data (Not repeatable)
- \$7 Script of cataloguing and script of the base access point (Not repeatable)
- \$8 Language of cataloguing and language of the base access point (Not repeatable)

540 Related Access Point – Name/Title (Repeatable)

Indicators: blank

A) Subfields: Embedded Fields Technique**Data Subfields**

- \$1 Linking data (Repeatable)

Control Subfields

- \$0 Instruction phrase (Not repeatable)
- \$2 System code (Not repeatable)
- \$3 Authority record identifier (Not repeatable)
- \$5 Relationship control (Not repeatable)
- \$6 Interfield linking data (Not repeatable)
- \$7 Script of cataloguing and script of the base access point (Not repeatable)
- \$8 Language of cataloguing and language of the base access point (Not repeatable)

B) Subfields: Standard Subfields Technique**Data Subfields**

- \$a Entry Element (Not repeatable)
- \$t Title (Not repeatable)
- \$j Form subdivision (Repeatable)
- \$x Topical subdivision (Repeatable)
- \$y Geographical subdivision (Repeatable)
- \$z Chronological subdivision (Repeatable)

Control Subfields

- \$7 Script of cataloguing and script of the base access point (Not repeatable)
- \$8 Language of cataloguing and language of the base access point (Not repeatable)

543 Related Access Point – Conventional Name/Title for Legal and Religious Texts (Repeatable)

Indicator 1: blank

Indicator 2: specifies the form of conventional name/title:

- 1 Name entered under country or other geographical name
- 2 Name entered under other form

Data Subfields

- \$a Entry element (Not repeatable)
- \$b Subdivision (Repeatable)
- \$c Addition to name or qualifier (Repeatable)
- \$e Name of the other party (Not repeatable)
- \$f Date of legal issue or version, or date of the signing (Repeatable)
- \$i Name of section or part (Repeatable)
- \$l Form subheading (Repeatable)
- \$n Miscellaneous information (Repeatable)
- \$t Conventional title (Not repeatable)
- \$j Form subdivision (Repeatable)
- \$x Topical subdivision (Repeatable)
- \$y Geographical subdivision (Repeatable)
- \$z Chronological subdivision (Repeatable)

Control Subfields

- \$0 Instruction phrase (Repeatable)
- \$2 System code (Not repeatable)
- \$3 Authority record identifier (Not repeatable)
- \$5 Relationship control (Not repeatable)
- \$6 Interfield linking data (Repeatable)
- \$7 Script of cataloguing and script of the base access point (Not repeatable)
- \$8 Language of cataloguing and language of the base access point (Not repeatable)

545 Related Access Point – Name/Collective Title (Repeatable)

Indicators: blank

A) Subfields: Embedded Fields Technique**Data Subfields**

- \$1 Linking data (Repeatable)

Control Subfields

- \$0 Instruction phrase (Not repeatable)
- \$2 System code (Not repeatable)
- \$3 Authority record identifier (Not repeatable)
- \$5 Relationship control (Not repeatable)
- \$6 Interfield linking data (Not repeatable)
- \$7 Script of cataloguing and script of the base access point (Not repeatable)
- \$8 Language of cataloguing and language of the base access point (Not repeatable)

B) Subfields: Standard Subfields Technique**Data Subfields**

- \$a Name (Not repeatable)
- \$t Title (Not repeatable)
- \$j Form subdivision (Repeatable)
- \$x Topical subdivision (Repeatable)
- \$y Geographical subdivision (Repeatable)
- \$z Chronological subdivision (Repeatable)

Control Subfields

- \$7 Script of cataloguing and script of the base access point (Not repeatable)
- \$8 Language of cataloguing and language of the base access point (Not repeatable)

550 Related Access Point – Topical Subject (Repeatable)

Indicators: blank

Data Subfields

- \$a Topical subject (Not repeatable)
- \$n Subject category code (Repeatable)
- \$m Subject category subdivision code (Repeatable)
- \$j Form subdivision (Repeatable)
- \$x Topical subdivision (Repeatable)
- \$y Geographical subdivision (Repeatable)
- \$z Chronological subdivision (Repeatable)

Control Subfields

- \$0 Instruction phrase (Not repeatable)
- \$2 System code (Not repeatable)
- \$3 Authority record identifier (Not repeatable)
- \$5 Relationship control (Not repeatable)
- \$6 Interfield linking data (Not repeatable)
- \$7 Script of cataloguing and script of the base access point (Not repeatable)
- \$8 Language of cataloguing and language of the base access point (Not repeatable)

560 Related Access Point – Place and Date of Publication, Performance, Provenance, etc. (Repeatable)

Indicators: blank

Data Subfields

- \$a Country (nation state) (Not repeatable)
- \$b State or province, etc. (Not repeatable)
- \$c Intermediate political jurisdiction (Repeatable)
- \$d City, etc. (Not repeatable)
- \$e Venue (Repeatable)
- \$f Date (Repeatable)
- \$g Season (Not repeatable)
- \$h Occasion (Not repeatable)
- \$i Final date (Not repeatable)
- \$k Subsection of city, etc. (Repeatable)
- \$m Other geographical regions or features (Repeatable)
- \$n Extraterrestrial areas (Repeatable)
- \$o Geographical areas such as world, hemisphere, continent (Repeatable)

Control Subfields

- \$0 Instruction phrase (Not repeatable)
- \$2 System code (Not repeatable)
- \$3 Authority record identifier (Not repeatable)
- \$5 Relationship control (Not repeatable)
- \$6 Interfield linking data (Not repeatable)
- \$7 Script of cataloguing and script of the base access point (Not repeatable)
- \$8 Language of cataloguing and language of the base access point (Not repeatable)

580 Related Access Point – Form, Genre or Physical Characteristics (Repeatable)

Indicator 1: blank

Indicator 2: specifies the type of the entity:

- 0 Work
- 2 Manifestation
- 3 Item
- # Not defined

Data Subfields

- \$a Entry Element (Not repeatable)
- \$j Form Subdivision (Repeatable)
- \$x Topical Subdivision (Repeatable)
- \$y Geographical Subdivision (Repeatable)
- \$z Chronological Subdivision (Repeatable)

Control Subfields

- \$0 Instruction phrase (Not repeatable)
- \$2 System code (Not repeatable)
- \$3 Authority record identifier (Not repeatable)
- \$5 Relationship control (Not repeatable)
- \$6 Interfield linking data (Not repeatable)
- \$7 Script of cataloguing and script of the base access point (Not repeatable)
- \$8 Language of cataloguing and language of the base access point (Not repeatable)

6-- CLASSIFICATION AND ENTITY HISTORY BLOCK

640 Place(s) and Date(s) Associated with the Entity (Repeatable)

Indicator 1: specifies the type of information:

- # Blank (Applies to topical subject)
- 1 Beginning of existence (or birth)
- 2 End of existence (or death)
- 3 Activity
- 4 Residence
- 5 Creation of intellectual or artistic content
- 6 First presentation to a public
- 0 Other

Indicator 2: blank

Data Subfields

- \$a Country (Not repeatable)
- \$b State, region, etc. (Not repeatable)
- \$c County (Not repeatable)
- \$d City (Not repeatable)
- \$e Venue (Repeatable)
- \$f Date of beginning or unique date (Not repeatable)
- \$g Season (Not repeatable)
- \$h Occasion (Not repeatable)
- \$i Final date (Not repeatable)
- \$f/0 and \$i/0 Era (1 character. Mandatory)
 - # = CE
 - = BC
- \$f/1-8 and \$i/1-8 Date (8 characters)

\$f/9 and \$i/9 Date Reliability (1 character)
 # = certain date
 ? = uncertain date

Control Subfields

\$0 Instruction phrase (Not repeatable)

675 Universal Decimal Classification (UDC) (Repeatable)

Indicators: blank

Data Subfields

\$a UDC number, single or beginning of a range (Not repeatable)

\$b UDC number, end of a range (Not repeatable)

\$c Explanatory terms (Repeatable)

\$v UDC edition (Not repeatable)

\$z Language of edition (Not repeatable)

Control Subfields

\$3 Authority record identifier (Not repeatable)

676 Dewey Decimal Classification (DDC) (Repeatable)

Indicators: blank

Data Subfields

\$a DDC number, single or beginning of a range (Not repeatable)

\$b DDC number, end of a range (Not repeatable)

\$c Explanatory terms (Repeatable)

\$v DDC edition (Not repeatable)

\$z Language of edition (Not repeatable)

Control Subfields

\$3 Authority record identifier (Not repeatable)

680 Library of Congress Classification (LCC) (Repeatable)

Indicators: blank

Data Subfields

\$a LC number, single or beginning of a range (Not repeatable)

\$b LC number, end of a range (Not repeatable)

\$c Explanatory terms (Repeatable)

Control Subfields

\$3 Authority record identifier (Not repeatable)

686 Other Classification Numbers (Repeatable)

Indicators: blank

Data Subfields

\$a Class number, single or beginning of a range (Not repeatable)

\$b Class number, end of a range (Not repeatable)

\$c Explanatory terms (Repeatable)

Control Subfields

\$2 System code (Not repeatable)

\$3 Authority record identifier (Not repeatable)

7-- AUTHORIZED ACCESS POINT IN OTHER LANGUAGE AND/OR SCRIPT BLOCK**700 Authorized Access Point in Other Language and/or Script – Personal Name (Repeatable)**

Indicator 1: blank

Indicator 2: specifies the way the name is entered:

0 Name entered under forename or direct order

1 Name entered under surname

Data Subfields

\$a Entry element (Not repeatable)

\$b Part of name other than entry element (Not repeatable)

\$c Additions to names other than dates (Repeatable)

\$d Roman numerals (Not repeatable)

\$f Dates (Not repeatable)

\$g Expansion of initials of forename (Not repeatable)

\$4 Relator code (Repeatable)

\$j Form subdivision (Repeatable)

\$x Topical subdivision (Repeatable)

\$y Geographical subdivision (Repeatable)

\$z Chronological subdivision (Repeatable)

Control Subfields

\$2 System code (Not repeatable)

\$3 Authority record identifier (Not repeatable)

\$7 Script of cataloguing and script of the base access point (Not repeatable)

\$8 Language of cataloguing and the base access point (Not repeatable)

710 Authorized Access Point in Other Language and/or Script – Corporate Body Name (Repeatable)

Indicator 1: specifies the kind of corporate body:

0 Corporate name

1 Meeting

Indicator 2: specifies the way the names are entered:

0 Name in inverted form

1 Name entered under place or jurisdiction

2 Name entered under name in direct order

Data Subfields

\$a Entry element (Not repeatable)

\$b Subdivision (Repeatable)

\$c Addition to name or qualifier (Repeatable)

\$d Number of meeting and/or number of part of meeting (Not repeatable)

\$e Location of meeting (Not repeatable)

\$f Date of meeting (Not repeatable)

\$g Inverted element (Not repeatable)

\$h Part of name other than entry element and inverted element (Not repeatable)

\$4 Relator code (Repeatable)

\$j Form subdivision (Repeatable)

\$x Topical subdivision (Repeatable)

- \$y Geographical subdivision (Repeatable)
- \$z Chronological subdivision (Repeatable)

Control Subfields

- \$2 System code (Not repeatable)
- \$3 Authority record identifier (Not repeatable)
- \$7 Script of cataloguing and script of the base access point (Not repeatable)
- \$8 Language of cataloguing and language of the base access point (Not repeatable)

715 Authorized Access Point in Other Language and/or Script – Territorial or Geographical Name (Repeatable)

Indicators: blank

Data Subfields

- \$a Entry element (Not repeatable)
- \$j Form subdivision (Repeatable)
- \$x Topical subdivision (Repeatable)
- \$y Geographical subdivision (Repeatable)
- \$z Chronological subdivision (Repeatable)

Control Subfields

- \$2 System code (Not repeatable)
- \$3 Authority record identifier (Not repeatable)
- \$7 Script of cataloguing and script of the base access point (Not repeatable)
- \$8 Language of cataloguing and language of the base access point (Not repeatable)

716 Authorized Access Point in Other Language and/or Script – Trademark (Repeatable)

Indicators: blank

Data Subfields

- \$a Data element (Not repeatable)
- \$f Dates (Not repeatable)
- \$c Qualification (Repeatable)
- \$j Form, genre or physical characteristic subdivision (Repeatable)
- \$x Topical subdivision (Repeatable)
- \$y Geographical subdivision (Repeatable)
- \$z Chronological subdivision (Repeatable)

Control Subfields

- \$2 System code (Not repeatable)
- \$3 Authority record identifier (Not repeatable)
- \$7 Script of cataloguing and script of the base access point (Not repeatable)
- \$8 Language of cataloguing and language of the base access point (Not repeatable)

717 Authorized Access Point in Other Language and/or Script – Printer/Publisher Device (Repeatable)

Indicators: blank

Data Subfields

- \$a Printer/publisher device description (Not repeatable)
- \$b Motto (Repeatable)
- \$c Standard citation (Repeatable)
- \$d Size (Not repeatable)

- \$f Date (Not repeatable)
- \$g Iconographic term (Repeatable)
- \$j Form subdivision (Repeatable)
- \$x Topical subdivision (Repeatable)
- \$y Geographical subdivision (Repeatable)
- \$z Chronological subdivision (Repeatable)

Control Subfields

- \$2 System code (Not repeatable)
- \$3 Authority record identifier (Not repeatable)
- \$7 Script of cataloguing and script of the base access point (Not repeatable)
- \$8 Language of cataloguing and language of the base access point (Not repeatable)

720 Authorized Access Point in Other Language and/or Script – Family Name (Repeatable)

Indicators: blank

Data Subfields

- \$a Entry element (Not repeatable)
- \$c Type of family (Not repeatable)
- \$d Places associated with the family (Repeatable)
- \$f Dates (Not repeatable)
- \$4 Relator code (Repeatable)
- \$j Form subdivision (Repeatable)
- \$x Topical subdivision (Repeatable)
- \$y Geographical subdivision (Repeatable)
- \$z Chronological subdivision (Repeatable)

Control Subfields

- \$2 System code (Not repeatable)
- \$3 Authority record identifier (Not repeatable)
- \$7 Script of cataloguing and script of the base access point (Not repeatable)
- \$8 Language of cataloguing and language of the base access point (Not repeatable)

730 Authorized Access Point in Other Language and/or Script – Title (Repeatable)

Indicators: blank

Data Subfields

- \$a Entry element (Not repeatable)
- \$b General material designation (Repeatable)
- \$h Number of section or part (Repeatable)
- \$i Name of section or part (Repeatable)
- \$k Date of publication (Not repeatable)
- \$l Form subdivision (Not repeatable)
- \$m Language (Not repeatable)
- \$n Miscellaneous information (Repeatable)
- \$q Version (or date of version) (Not repeatable)
- \$r Medium of performance (for music) (Repeatable)
- \$s Numeric designation (for music) (Repeatable)
- \$u Key (for music) (Not repeatable)
- \$w Arranged statement (for music) (Not repeatable)
- \$j Form subdivision (Repeatable)

- \$x Topical subdivision (Repeatable)
- \$y Geographical subdivision (Repeatable)
- \$z Chronological subdivision (Repeatable)

Control Subfields

- \$2 System code (Not repeatable)
- \$3 Authority record identifier (Not repeatable)
- \$7 Script of cataloguing and script of the base access point (Not repeatable)
- \$8 Language of cataloguing and language of the base access point (Not repeatable)

740 Authorized Access Point in Other Language and/or Script – Name/Title (Repeatable)

Indicators: blank

A) Subfields: Embedded Fields Technique**Data Subfields**

- \$1 Linking data (Repeatable)

Control Subfields

- \$2 System code (Not repeatable)
- \$3 Authority record identifier (Not repeatable)
- \$7 Script of cataloguing and script of the base access point (Not repeatable)
- \$8 Language of cataloguing and language of the base access point (Not repeatable)

B) Subfields: Standard Subfields Technique**Data Subfields**

- \$a Name (Not repeatable)
- \$t Title (Not repeatable)
- \$j Form subdivision (Repeatable)
- \$x Topical subdivision (Repeatable)
- \$y Geographical subdivision (Repeatable)
- \$z Chronological subdivision (Repeatable)

Control Subfields

- \$7 Script of cataloguing and script of the base access point (Not repeatable)
- \$8 Language of cataloguing and language of the base access point (Not repeatable)

743 Authorized Access Point in Other Language and/or Script – Conventional Name/Title for Legal and Religious Texts (Repeatable)

Indicator 1: blank

Indicator 2: specifies the form of conventional name/title:

- 1 Name entered under country or other geographical name
- 2 Name entered under other form

Data Subfields

- \$a Entry Element (Not repeatable)
- \$b Subdivision (Repeatable)
- \$c Addition to name or qualifier (Repeatable)
- \$e Name of the other party (Not repeatable)
- \$f Date of legal issue or version, or date of the signing (Repeatable)
- \$i Name of section or part (Repeatable)
- \$l Form subheading (Repeatable)
- \$n Miscellaneous information (Repeatable)

- \$t Conventional title (Not repeatable)
- \$j Form subdivision (Repeatable)
- \$x Topical subdivision (Repeatable)
- \$y Geographical subdivision (Repeatable)
- \$z Chronological subdivision (Repeatable)

Control Subfields

- \$2 System code (Not repeatable)
- \$3 Authority record identifier (Not repeatable)
- \$7 Script of cataloguing and script of the base access point (Not repeatable)
- \$8 Language of cataloguing and language of the base access point (Not repeatable)

745 Authorized Access Point in Other Language and/or Script – Name/Collective Title (Repeatable)

Indicators: blank

A) Subfields: Embedded Fields Technique**Data Subfields**

- \$1 Linking data (Repeatable)

Control Subfields

- \$2 System code (Not repeatable)
- \$3 Authority record identifier (Not repeatable)
- \$7 Script of cataloguing and script of the base access point (Not repeatable)
- \$8 Language of cataloguing and language of the base access point (Not repeatable)

B) Subfields: Standard Subfields Technique**Data Subfields**

- \$a Name (Not repeatable)
- \$t Title (Not repeatable)
- \$j Form subdivision (Repeatable)
- \$x Topical subdivision (Repeatable)
- \$y Geographical subdivision (Repeatable)
- \$z Chronological subdivision (Repeatable)

Control Subfield

- \$7 Script of cataloguing and script of the base access point (Not repeatable)
- \$8 Language of cataloguing and language of the base access point (Not repeatable)

750 Authorized Access Point in Other Language and/or Script – Topical Subject (Repeatable)

Indicators: blank

Data Subfields

- \$a Topical subject (Not repeatable)
- \$n Subject category code (Repeatable)
- \$m Subject category subdivision code (Repeatable)
- \$j Form subdivision (Repeatable)
- \$x Topical subdivision (Repeatable)
- \$y Geographical subdivision (Repeatable)
- \$z Chronological subdivision (Repeatable)

Control Subfields

- \$2 System code (Not repeatable)

- \$3 Authority record identifier (Not repeatable)
- \$7 Script of cataloguing and script of the base access point (Not repeatable)
- \$8 Language of cataloguing and language of the base access point (Not repeatable)

760 Authorized Access Point in Other Language and/or Script – Place and Date of Publication, Performance, Provenance, etc. (Repeatable)

Indicators: blank

Data Subfields

- \$a Country (nation state) (Not repeatable)
- \$b State or province, etc. (Not repeatable)
- \$c Intermediate political jurisdiction (Repeatable)
- \$d City, etc. (Not repeatable)
- \$e Venue (Repeatable)
- \$f Date (Repeatable)
- \$g Season (Not repeatable)
- \$h Occasion (Not repeatable)
- \$i Final date (Not repeatable)
- \$k Subsection of city, etc. (Repeatable)
- \$m Other geographical regions or features (Repeatable)
- \$n Extraterrestrial areas (Repeatable)
- \$o Geographical areas such as world, hemisphere, continent (Repeatable)

Control Subfields

- \$2 System code (Not repeatable)
- \$3 Authority record identifier (Not repeatable)
- \$7 Script of cataloguing and script of the base access point (Not repeatable)
- \$8 Language of cataloguing and language of the base access point (Not repeatable)

780 Authorized Access Point in Other Language and/or Script – Form, Genre or Physical Characteristics (Repeatable)

Indicator 1: blank

Indicator 2: specifies the type of the entity:

- # Not defined
- 0 Work
- 2 Manifestation
- 3 Item

Data Subfields

- \$a Entry Element (Not repeatable)
- \$j Form Subdivision (Repeatable)
- \$x Topical Subdivision (Repeatable)
- \$y Geographical Subdivision (Repeatable)
- \$z Chronological Subdivision (Repeatable)

Control Subfields

- \$2 System code (Not repeatable)
- \$3 Authority record identifier (Not repeatable)
- \$7 Script of cataloguing and script of the base access point (Not repeatable)
- \$8 Language of cataloguing and language of the base access point (Not repeatable)

8-- SOURCE INFORMATION BLOCK**801 Originating Source (Mandatory in case of exchange of bibliographic data. Repeatable)**

Indicator 1: blank

Indicator 2: specifies the function performed by the agency:

0 Original cataloguing agency

1 Transcribing agency

2 Modifying agency

3 Issuing agency

Subfields

\$a Country (Not repeatable)

\$b Agency (Not repeatable)

\$c Date of latest transaction (Not repeatable)

\$2 System code (Not repeatable)

810 Source Data Found (Repeatable)

Indicators: blank

Subfields

\$a Citation (Not repeatable)

\$b Information found (Not repeatable)

815 Source Data Not Found (Not repeatable)

Indicators: blank

Subfields

\$a Citations (Repeatable)

820 Usage or Scope Information (Repeatable)

Indicators: blank

Subfields

\$a Note text (Repeatable)

825 Example Under Note (Repeatable)

Indicators: blank

Subfields

\$a Note text (Not repeatable)

830 General Cataloguer's Note (Repeatable)

Indicators: blank

Subfields

\$a Note text (Repeatable)

835 Deleted Access Point Information (Repeatable)

Indicators: blank

Subfields

\$a Note text (Repeatable)

\$b Replacement access point (Repeatable)

\$d Date of the transaction (Mandatory if field is used. Not repeatable)

836 Replaced Access Point Information (Not repeatable)

Indicators: blank

Subfields

- \$b Replaced access point (Mandatory when field is used. Not repeatable)
- \$d Date of the transaction (Mandatory when field is used. Not repeatable)

856 Electronic Location and Access (Repeatable)

Indicator 1: specifies the access method:

- # No information provided
- 0 Email
- 1 FTP
- 2 Remote login (Telnet)
- 3 Dial-up
- 4 HTTP
- 7 Method specified in subfield \$y

Indicator 2: blank

Subfields

- \$a Host name (Repeatable)
- \$b Access number (Repeatable)
- \$c Compression information (Repeatable)
- \$d Path (Repeatable)
- \$e Date and hour of consultation and access (Not repeatable)
- \$f Electronic name (Repeatable)
- \$g Uniform Resource Name (Repeatable)
- \$h Processor of request (Not repeatable)
- \$i Instruction (Repeatable)
- \$j Bits per second (Not repeatable)
- \$k Password (Not repeatable)
- \$l Logon/login (Not repeatable)
- \$m Contact for access assistance (Repeatable)
- \$n Name of location of host in subfield \$a (Not repeatable)
- \$o Operating system (Not repeatable)
- \$p Port (Not repeatable)
- \$q Electronic format type (Not repeatable)
- \$r Settings (Not repeatable)
- \$s File size (Repeatable)
- \$t Terminal emulation (Repeatable)
- \$u Uniform Resource Locator (Not repeatable)
- \$v Hours access method available (Repeatable)
- \$w Record control number (Repeatable)
- \$x Nonpublic note (Repeatable)
- \$y Access method (Not repeatable)
- \$z Public note (Repeatable)

886 Data Not Converted From Source Format (Repeatable)

Indicator 1: specifies the type of field:

- 0 Record Label
- 1 Variable control field (0-- fields without indicators or subfields)
- 2 Variable data field (010-999 fields)

Indicator 2: blank

Subfields

- \$a Tag of the source format field (Not repeatable)

- \$b Indicators and subfields of the source format field (Not repeatable)
- \$2 System code (Not repeatable)

9-- NATIONAL USE BLOCK

All -9- and --9 fields throughout the format are reserved for national and local use; their definitions and indicator and subfield values remain undefined by the Permanent UNIMARC Committee. This is also true of indicator value 9 and subfield \$9.